

Enrollacables

H05VV-F/ H05RR-F 3G1.5
10, 15, 25, 50 metros



6620006001



6620006003



6620006004



6620006006

6620006005

MODELOS

Código	Descripción	Tipo cable	Longitud	Dimensiones
6620006001	Bultmeier enrollacables	H05VV-F 3G1.5	10 m	220x70x280 mm
6620006003	Bultmeier enrollacables	H05VV-F 3G1.5	15 m	180x150x270 mm
6620006004	Bultmeier enrollacables	H05VV-F 3G1.5	25 m	230x170x320 mm
6620006005	Bultmeier enrollacables	H05VV-F 3G1.5	50 m	270x180x370 mm
6620006006	Bultmeier enrollacables con protección de tomas	H05RR-F 3G1.5	25 m	230x170x320 mm

CARACTERÍSTICAS TÉCNICAS

Enrollacables 4 tomas con disyuntor (excepto modelo 6620006006)

Tensión de funcionamiento	250 V
Intensidad máxima	16 A
Potencia máxima	3200 W completamente extendido
Resistencia al impacto	IK06
Hilo incandescente	750°C partes activas, 650°C resto
Estabilidad dimensional	-15°C~+70°C
Grado de protección	IP20 (modelo 6620006006 IP44)
Protección infantil	Sí
Normas	EN 61242
Certificados	CE, ROHS, GS

